

ErisTerminal™ Accessory DECT Repeater

VSP605A

- Extends the DECT coverage
- Supports up to 5 DECT Repeaters on one base station
- Works with VSP600A/610A
- Supports 2 concurrent calls per Repeater¹
- One tri-colour LED indicator
- Supports automatic handover of calls between cells
- Easy installation
- Wall mountable



Specifications, weights & dimensions


RF frequency band: 1881.792 - 1897.344 MHz	Giftbox dimensions (WxDxH): 118mm x 80mm x 175mm
Operating temperature: 0 - 50 °C (32 - 122 °F)	Giftbox weight: 0.252kg
Colour: Black	Master pack dimensions (WxDxH): 251mm x 175mm x 195mm
Product dimensions (WxDxH): 115mm x 115mm x 40mm	Master pack weight: 1.28kg
Product weight: 0.133kg	Quantity: 4

AC Adapter specifications, weights & dimensions

AC adapter rating: 6VDC 450mA
Colour: Black
Product dimensions (WxDxH): 49.5mm x 48.7mm x 26.5mm
Product weight: 0.0586kg

Contact Us

VTech SIP Phones UK

 www.ukbusinessphones.vtech.com

 01706 694070

 enquiries_ukbusinessphones@vtech.com

¹ The total number of concurrent calls that VSP600A/610A can be supported is 4.

